



The GCP-020 is a clamp-type probe for measuring AC and DC current waveforms. Ranging from 100mA to 200A, the GCP-020 is designed to perform high current measurement in a compact package.

### Clamp to Measure : Safe and Easy

To perform current waveform measurement, just clamp the jaw around the conductor-under-test and connect its lead to the BNC input of an oscilloscope. Breaking the circuit and connecting an ammeter in series is no longer necessary.

### Current Measurement from 40Hz to 10kHz for Various Instruments

Using the combination of a Hall-effect sensor and an AC current transformer, the GCP-020 provides accurate measurement from 40Hz to 10kHz. The dual measurement range spans 100mA~20A and 500mA~200A. In addition to oscilloscopes, the GCP-020 can also be connected to multimeters and data loggers.

## GCP-020

### FEATURES

- Bandwidth : 40Hz ~ 10kHz
- Measurement Range :  
100mA ~ 20A and 500mA ~ 200A
- Accuracy :  $\leq 2\%$  (100mA ~ 20A)  
 $\leq 1.5\%$  (500mA ~ 200A)
- Jaw Opening : 21mm Diameter

### APPLICATIONS

- Harmonic Current Measurement
- Inrush Current Measurement
- Current Ripple and Noise Measurement
- Power Quality Analysis

## SPECIFICATIONS

	<b>GCP-020</b>
<b>Bandwidth</b>	40Hz ~ 10kHz
<b>Ratio</b>	100mA ~ 20A 500mA ~ 200A
<b>Accuracy</b>	≤ 2% ( 100mA ~ 20A peak ) ≤ 1.5% ( 500mA ~ 200A peak )
<b>Nominal Measuring Scope</b>	500mA ~ 200A and 100mA ~ 20A
<b>Ratio Input/Output</b>	1A ~ / 10mV ~ and 1A ~ / 1000mV
<b>Sinusoidal Current</b>	48 ~ 65Hz
<b>Connection</b>	BNC
<b>Direct Current</b>	No
<b>Temperature &amp; Humidity Range (Guaranteed Accuracy)</b>	20 ~ 26°C, relative humidity ; 20 ~ 75% (no condensation)
<b>Continuous Magnetic Field</b>	Earth Field (< 40A / m)
<b>Proximity of External Conductors</b>	No current
<b>Measuring Device Impedance</b>	> 1 MW and < 100pF
<b>Max. Clamping Capacity</b>	∅20mm cable or 20 x 5mm bar
<b>Location for Use</b>	Altitude up to 2000m, Indoors
<b>Dimension</b>	135(W) x 50(H) x 30(D) mm
<b>Open Jaw Height</b>	69mm
<b>Weight</b>	Approx. 180g
<b>Jaw Opening</b>	21mm

## ORDERING INFORMATION

**GCP-020** 10KHz/200A A.C./D.C. Current Probe

Global Headquarters

**GOOD WILL INSTRUMENT CO., LTD.**

No.7-1, Jhongsing Road, Tucheng Dist., New Taipei City 236, Taiwan  
T +886-2-2268-0389 F +886-2-2268-0639  
E-mail: marketing@goodwill.com.tw

China Subsidiary

**GOOD WILL INSTRUMENT (SUZHOU) CO., LTD.**

NO. 69, Lushan Road, Snd, Suzhou Jiangsu 215011 China  
T +86-512-6661-7177 F +86-512-6661-7277  
E-mail: marketing@instek.com.cn

Malaysia Subsidiary

**GOOD WILL INSTRUMENT (M) SDN. BHD.**

27, Persiaran Mahsuri 1/1, Sunway Tunas,  
11900 Bayan Lepas, Penang, Malaysia  
T +604-6309988 F +604-6309989  
E-mail: sales@goodwill.com.my

U.S.A. Subsidiary

**INSTEK AMERICA CORP.**

3661 Walnut Avenue Chino, CA 91710, U.S.A.  
T +1-909-5918358 F +1-909-5912280  
E-mail: sales@instekamerica.com

Japan Subsidiary

**INSTEK JAPAN CORPORATION**

4F, Prosper Bldg, 1-3-3 Iwamoto-Cho Chiyoda-Ku,  
Tokyo 101-0032 Japan  
T +81-3-5823-5656 F +81-3-5823-5655  
E-mail: info@instek.co.jp

Korea Subsidiary

**GOOD WILL INSTRUMENT KOREA CO., LTD.**

Room No.805, Ace Hightech-City B/D 1Dong,  
Mullae-Dong 3Ga 55-20, Yeongduengpo-Gu, Seoul, Korea  
T +82-2-3439-2205 F +82-2-3439-2207  
E-mail : gwinstek@gwinstek.co.kr

**GW INSTEK**  
Simply Reliable

[www.gwinstek.com](http://www.gwinstek.com)